

# BOND TAC 800™

SOLVENT & LUBRICANT FOR USE WITH BOND TAC 1500

## DESCRIPTION

**BondTAC™ 800** is a unique blend of liquids for use in adjusting the viscosity of BondTAC™ 1500 and for lubricating BondTAC™ coated surfaces in order to adhere components and boards that require movement for adjustment.

## WHERE TO USE

**AS WITH ALL FLAMMABLE, SOLVENT-BASED PRODUCTS, EXERCISE CAUTION WHEN USING THIS PRODUCT.**

BondTAC™ 800 Diluent and Surface Lubricant will permit adjustments to BondTAC™ 1500 coated surfaces in order to attain the proper fit of components and boards. Allow a minimum of one hour drying time after application of BondTAC™ 1500, and then apply a sparing coat of BondTAC™ 800 to the surface of the BondTAC™ 1500, using a brush or paint roller. Slide and fit the board or component into place within five minutes of BondTAC™ 800 application.

In some instances, such as sub-zero temperatures, or where BondTAC™ 1500 has been permitted to evaporate, viscosity may be adjusted by slight addition of BondTAC™ 800.

When necessary, use BondTAC™ 800 solvent to clean dried BondTAC™ 1500 Low-VOC Waterproof Elastomeric Adhesive Membrane from brushes, tools, fabrics, etc. It can also be used to remove oil, wax and grease from most finishes and may be used to remove bonded laminates.

## CONDITIONS & LIMITATIONS

This product contains solvents that if not handled according to the following instructions, may be harmful to the health of the user. **Always use only in well ventilated conditions and with good air circulation.** Use a respirator if in doubt. Safety glasses and gloves should be used.

## PERFORMANCE & COMPLIANCE:

Appearance & Odour	Clear, colourless liquid with solvent odour
Specific Gravity	0.83
Flash Point	-11°C
Flammability	Extremely Flammable

## APPLICATION INSTRUCTIONS

**WARNING! EXTREMELY FLAMMABLE! VAPOURS MAY IGNITE EXPLOSIVELY! VAPOURS HARMFUL! MAY IRRITATE EYES AND SKIN! USE ONLY IN WELL VENTILATED CONDITIONS! KEEP OUT OF REACH OF CHILDREN!**

Open all windows and doors to prevent buildup of vapours. Keep away from heat, sparks or open flame. Do not smoke. Extinguish all flames and pilot lights. Turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapours are gone. Do not use in areas where static electrical sparks may be generated. Keep container tightly closed when not in use. Store in a cool, dry place.

To clean up dried adhesive, apply a generous amount of this product on the dry adhesive with the use of a soft cloth. Allow the solvent a few minutes to penetrate then wipe dry. Rinse brushes and tools thoroughly with this solvent if the adhesive is still wet. Allow tools and brushes to soak if adhesive has dried on them.

To remove bonded laminate, apply BondTAC™ 800 solvent directly on the dry adhesive glue line then slowly lift the laminate away. Keep applying solvent as the laminate is peeled away.

BondTAC™ waterproof adhesive membranes are supplied ready-to-use and should only be diluted or thinned down if the container has been left open and the adhesive has thickened to a point where it is not easily applied by brush or roller. Use as needed when necessary.

## WARRANTY

Before using, the user shall determine the suitability of the product for its intended use and the user alone assumes all risks and liabilities whatsoever in connection therewith. Bondtac Technologies Incorporated assumes no responsibility for personal injury or property damage to vendees or users or third parties, caused by the improper use of this product. Such vendees or users assume all risks with the use of the material.